

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY INFORMATION

Product Name:

GT PLUS WITH ETHANOL

Manufacturer Information:

Sunoco, Inc. (R&M) Ten Penn Center 1801 Market Street Philadelphia, Pennsylvania, 19103-1699

Product Use:

Racing fuel

Emergency Phone Numbers:

Chemtrec	(800) 424-9300
Sunoco Inc.	(800) 964-8861

Information:

Product Safety Information	(610) 859-1120
----------------------------	----------------

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No.	Amount (Vol%)
LIGHT PETROLEUM DISTILLATE	8006-61-9	0 - 99.9
XYLENE	1330-20-7	0 - 25
TOLUENE	108-88-3	20 - 20
ETHYL ALCOHOL	64-17-5	13 - 13
TERT-BUTYL ALCOHOL	75-65-0	0 - 10
CYCLOHEXANE	110-82-7	0 - 9
1,2,4-TRIMETHYLBENZENE	95-63-6	0 - 5
ETHYL BENZENE	100-41-4	0 - 5
N-HEXANE	110-54-3	0 - 5
NAPHTHALENE	91-20-3	0 - 5
BENZENE	71-43-2	0.1 - 4.9
2,6-DI-TERT-BUTYLPHENOL	128-39-2	1.4 - 1.4
CUMENE	98-82-8	0 - 1

EXPOSURE GUIDELINES (SEE SECTION 15 FOR ADDITIONAL EXPOSURE LIMITS)

	CAS No.	Governing Body	Exposure Limits		
BENZENE	71-43-2	ACGIH	STEL	2.5	ppm
BENZENE	71-43-2	OSHA	STEL	5	ppm
BENZENE	71-43-2	ACGIH	TWA	0.5	ppm
BENZENE	71-43-2	OSHA	TWA	1	ppm
CUMENE	98-82-8	ACGIH	TWA	50	ppm
CUMENE	98-82-8	OSHA	TWA	50	ppm
CYCLOHEXANE	110-82-7	ACGIH	TWA	100	ppm

CYCLOHEXANE	110-82-7	OSHA	TWA	300	ppm
ETHYL ALCOHOL	64-17-5	ACGIH	TWA	1000	ppm
ETHYL ALCOHOL	64-17-5	OSHA	TWA	1000	ppm
ETHYL BENZENE	100-41-4	ACGIH	STEL	125	ppm
ETHYL BENZENE	100-41-4	ACGIH	TWA	100	ppm
ETHYL BENZENE	100-41-4	OSHA	TWA	100	ppm
N-HEXANE	110-54-3	ACGIH	TWA	50	ppm
N-HEXANE	110-54-3	OSHA	TWA	500	ppm
NAPHTHALENE	91-20-3	ACGIH	STEL	15	ppm
NAPHTHALENE	91-20-3	ACGIH	TWA	10	ppm
NAPHTHALENE	91-20-3	OSHA	TWA	10	ppm
TOLUENE	108-88-3	OSHA	С	300	ppm
TOLUENE	108-88-3	Sunoco	STEL	150	ppm
TOLUENE	108-88-3	NIOSH	STEL	150	ppm
TOLUENE	108-88-3	ACGIH	TWA	50	ppm
TOLUENE	108-88-3	OSHA	TWA	200	ppm
XYLENE	1330-20-7	ACGIH	STEL	150	ppm
XYLENE	1330-20-7	ACGIH	TWA	100	ppm
XYLENE	1330-20-7	OSHA	TWA	100	ppm
LIGHT PETROLEUM	8006-61-9	ACGIH	STEL	500	ppm
DISTILLATE					
LIGHT PETROLEUM	8006-61-9	ACGIH	TWA	300	ppm
DISTILLATE					
TERT-BUTYL ALCOHOL	75-65-0	ACGIH	TWA	100	ppm
TERT-BUTYL ALCOHOL	75-65-0	OSHA	TWA	100	ppm

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Danger! Extremely flammable liquid and vapor. Vapors may cause flash fire or explosion. Harmful or fatal if swallowed. Pulmonary aspiration hazard. After ingestion, may enter lungs and produce damage. Harmful if inhaled. High vapor concentrations may cause drowsiness. May cause skin irritation. May cause eye irritation. Contains material or materials that can cause birth defects. Contains material or materials that can cause cancer.

Hazards Ratings:

Key: 0 = least, 1 = slight, 2 = moderate, 3 = high, 4 = extreme					
	<u>Health</u>	Fire	Reactivity	<u>PPI</u>	
NFPA	1	3	0		
HMIS	2	4	0	Х	

• POTENTIAL HEALTH EFFECTS

PRE-EXISTING MEDICAL CONDITIONS

The following diseases or disorders may be aggravated by exposure to this product: Skin; Eye; Blood forming organs; Nervous system, Respiratory system; Lung (asthma-like conditions); Cardiovascular system,

INHALATION

Can cause severe central nervous system depression (including unconsciousness). May cause headaches and dizziness. Repeated excessive exposures may cause blood disorders such as anemia and leukemia. Contains a material that has been related to cancer in humans.

LC50 (mg/l):	no data
LC50 (mg/m3):	no data
LC50 (ppm):	no data

SKIN

May be absorbed through the skin in harmful amounts. Moderately irritating to the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

Draize Skin Score:	no data
LD50 (mg/kg):	no data

EYES

Moderately irritating to the eyes.

INGESTION

Product may be harmful or fatal if swallowed. Pulmonary aspiration hazard. After ingestion, may enter lungs and produce damage. Irritating to mouth, throat, and stomach. Contains material or materials that can cause birth defects.

LD50 (g/kg): no data

4. FIRST AID MEASURES

• INHALATION

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen and continue to monitor. Get immediate medical attention.

- SKIN
 - Wash with soap and water. Get medical attention if irritation develops or persists. Wash clothing before reuse.
- EYES

Flush eye with water for 15 minutes. Get medical attention.

INGESTION

Do not induce vomiting! Do not give liquids! Get medical attention immediately.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

Water spray; Alcohol resistant foam; Dry chemical; Carbon dioxide;

FIRE FIGHTING INSTRUCTIONS
 Use water spray to cool fire exposed tanks and containers. Wear structural fire fighting gear.

FLAMMABLE PROPERTIES

	Typical	Minimum	Maximum	Text Result	Units	Method
Flash Point				Minus 40 est'd	F	N/A
Autoignition Temperature				750 estimated	F	N/A
Lower Explosion Limit	1.5				%	N/A
Upper Explosion Limit	7.6				%	N/A

6. ACCIDENTAL RELEASE MEASURES

Prevent ignition, stop leak and ventilate the area. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Vapor can be controlled using a water fog. Water streams should not be directed to the liquid as this will cause the liquid to boil and generate more vapor. Keep personnel upwind from leak. Use appropriate personal protective equipment as stated in Section 8 of this MSDS. Advise the Environmental Protection Agency (EPA) and appropriate state agencies, if required. Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Vacuum or sweep up material and place in a disposal container.

7. HANDLING AND STORAGE

HANDLING

Use only in a well-ventilated area. Ground and bond containers when transferring material. NFPA class IA storage. Flash point is less than 73 degrees F and boiling point is less than 100 degrees F. Avoid breathing (dust, vapor, mist, gas). Avoid prolonged or repeated contact with skin. Avoid contact with eyes. Wash thoroughly after handling. Never siphon by mouth.

STORAGE

Keep away from heat, sparks, and flame. Keep container closed when not in use. Consult NFPA and / or OSHA codes for additional information.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Consult With a Health and Safety Professional for Specific Selections

ENGINEERING CONTROLS

Use with adequate ventilation. Ventilation is normally required when handling or using this product to keep exposure to airborne contaminants below the exposure limit. Use explosion-proof ventilation equipment.

PERSONAL PROTECTION

EYE PROTECTION

Use chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent).

GLOVES or HAND PROTECTION The glove(s) listed below may provide protection against permeation. Gloves of other chemically resistant materials may not provide adequate protection. Protective gloves are recommended to protect against contact with product. Polvethylene: Neoprene: Nitrile: Polvvinyl alcohol: Viton:

RESPIRATORY PROTECTION

Concentration in air determines the level of respiratory protection needed. Use only NIOSH certified respiratory equipment. Half-mask air purifying respirator with organic vapor cartridges is acceptable for exposures to ten (10) times the exposure limit. Full-face air purifying respirator with organic vapor cartridges is acceptable for exposures to ten exposures to fifty (50) times the exposure limit. Exposure should not exceed the cartridge limit of 1000 ppm. Protection by air purifying respirators is limited. Use a positive pressure-demand full-face supplied air respirator or SCBA for exposures greater than fifty (50) times the exposure limit. If exposure is above the IDLH (Immediately Dangerous to Life and Health) or there is the possibility of an uncontrolled release, or exposure levels are unknown, then use a positive pressure-demand full-face supplied air respirator with escape bottle or SCBA. Wear a NIOSH-approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions.

OTHER

Where splashing is possible, full chemically resistant protective clothing (e.g., acid suit) and boots are required. The following materials are acceptable for use as protective clothing: Polyethylene; Polyvinyl alcohol (PVA); Neoprene; Nitrile; Viton; Polyurethane; Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Remove contaminated clothing and wash before reuse. For non-fire emergencies, positive pressure SCBA and structural firefighter's protective clothing will provide only limited protection.

Physical Property	Typical	Units	Text Result	Reference
Appearance		N/A	Blue liquid	
Boiling Point		F	100 - 430	
Bulk Density	6.16	lb/gal		
Melting Point		F	no data	
Molecular Weight		g/mole	no data	
Octanol/Water Coefficient		N/A	no data	
рН		N/A	no data	
Specific Gravity	0.7408	N/A		
Solubility In Water		wt %	Nil to 15%	
Odor		N/A	Gasoline odor	
Odor Threshold		ppm	< 1	
Vapor Pressure		mmHg	325 - 525	@ 20 C

9. PHYSICAL AND CHEMICAL PROPERTIES

Viscosity (F)	SUS	no data	
Viscosity (C)	CsT	no data	
% Volatile	100 wt %		

10. STABILITY AND REACTIVITY

- STABILITY
- Stable
 CONDITIONS TO AVOID Avoid heat, sparks and open flame.
- INCOMPATIBILITY
 Strong oxidizers
- **HAZARDOUS DECOMPOSITION PRODUCTS** Combustion may produce carbon monoxide, carbon dioxide and other asphyxiants.
- HAZARDOUS POLYMERIZATION Will not polymerize.

11. ECOLOGICAL INFORMATION

Gasoline spills are toxic to fish and aquatic flora.

12. DISPOSAL CONSIDERATIONS

Follow federal, state and local regulations. This material is a RCRA hazardous waste. Do not flush material to drain or storm sewer. Contract to authorized disposal service.

13. TRANSPORT INFORMATION

<u>Governing Body</u>	<u>Mode</u>	Proper Shipping Name			
DOT	Ground	Gasoline			
<u>Governing Body</u> DOT	<u>Mode</u> Ground	<u>Hazard Class</u> 3 (Flammable liquid)	<u>UN/NA No.</u> 1203	<u>Label</u>	

14. REGULATORY INFORMATION

Regulatory List	Component	CAS No.
ACGIH - Occupational Exposure Limits - Carcinogens	BENZENE	71-43-2
ACGIH - Occupational Exposure Limits - Carcinogens	ETHYL ALCOHOL	64-17-5
ACGIH - Occupational Exposure Limits - Carcinogens	ETHYL BENZENE	100-41-4
ACGIH - Occupational Exposure Limits - Carcinogens	NAPHTHALENE	91-20-3
ACGIH - Occupational Exposure Limits - Carcinogens	TERT-BUTYL ALCOHOL	75-65-0
ACGIH - Occupational Exposure Limits - Carcinogens	TOLUENE	108-88-3
ACGIH - Occupational Exposure Limits - Carcinogens	XYLENE	1330-20-7
ACGIH - Occupational Exposure Limits - TWAs	BENZENE	71-43-2
ACGIH - Occupational Exposure Limits - TWAs	CUMENE	98-82-8
ACGIH - Occupational Exposure Limits - TWAs	CYCLOHEXANE	110-82-7
ACGIH - Occupational Exposure Limits - TWAs	ETHYL ALCOHOL	64-17-5
ACGIH - Occupational Exposure Limits - TWAs	ETHYL BENZENE	100-41-4
ACGIH - Occupational Exposure Limits - TWAs	N-HEXANE	110-54-3
ACGIH - Occupational Exposure Limits - TWAs	NAPHTHALENE	91-20-3
ACGIH - Occupational Exposure Limits - TWAs	TERT-BUTYL ALCOHOL	75-65-0
ACGIH - Occupational Exposure Limits - TWAs	TOLUENE	108-88-3
ACGIH - Occupational Exposure Limits - TWAs	XYLENE	1330-20-7
00000135300, GT PLUS WITH ETHANOL		5

ACGIH - Short Term Exposure Limits ACGIH - Skin Absorption Designation CAA (Clean Air Act) - HON Rule - Organic HAPs CAA (Clean Air Act) - HON Rule - Organic HAPs CAA (Clean Air Act) - HON Rule - Organic HAPs CAA (Clean Air Act) - HON Rule - Organic HAPs CAA (Clean Air Act) - HON Rule - Organic HAPs CAA (Clean Air Act) - HON Rule - Organic HAPs CAA (Clean Air Act) - HON Rule - Organic HAPs CAA (Clean Air Act) - HON Rule - SOCMI Chemicals CAA (Clean Air Act) - HON Rule - SOCMI Chemicals CAA (Clean Air Act) - HON Rule - SOCMI Chemicals CAA (Clean Air Act) - HON Rule - SOCMI Chemicals CAA (Clean Air Act) - HON Rule - SOCMI Chemicals CAA (Clean Air Act) - HON Rule - SOCMI Chemicals CAA (Clean Air Act) - HON Rule - SOCMI Chemicals CAA (Clean Air Act) - HON Rule - SOCMI Chemicals CAA - 1990 Hazardous Air Pollutants California - Prop. 65 - Developmental Toxicity California - Prop. 65 - Developmental Toxicity California - Prop. 65 - Developmental Toxicity California - Prop. 65 - Reproductive - Male California - Proposition 65 - Carcinogens List California - Proposition 65 - Carcinogens List Canada - WHMIS - Ingredient Disclosure CERCLA/SARA - Haz Substances and their RQs CERCLA/SARA - Haz Substances and their RQs

BENZENE	71-43-2
ETHYL BENZENE	100-41-4
LIGHT PETROLEUM	8006-61-9
DISTILLATE	
NAPHTHALENE	91-20-3
XYLENE	1330-20-7
BENZENE	71-43-2
N-HEXANE	110-54-3
NAPHTHALENE	91-20-3
TOLUENE	108-88-3
BENZENE	71-43-2
CUMENE	98-82-8
ETHYL BENZENE	100-41-4
N-HEXANE	110-54-3
NAPHTHALENE	91-20-3
TOLUENE	108-88-3
XYLENE	1330-20-7
BENZENE	71-43-2
CUMENE	98-82-8
CYCLOHEXANE	110-82-7
ETHYL BENZENE	100-41-4
N-HEXANE	110-54-3
NAPHTHALENE	91-20-3
TOLUENE	108-88-3
XYLENE	1330-20-7
BENZENE	71-43-2
	98-82-8
ETHYL BENZENE	100-41-4
	110-54-3
NAPHTHALENE TOLUENE	91-20-3
XYLENE	108-88-3 1330-20-7
BENZENE	71-43-2
ETHYL ALCOHOL	64-17-5
TOLUENE	108-88-3
BENZENE	71-43-2
BENZENE	71-43-2
NAPHTHALENE	91-20-3
1,2,4-TRIMETHYLBENZENE	95-63-6
BENZENE	71-43-2
CUMENE	98-82-8
CYCLOHEXANE	110-82-7
ETHYL ALCOHOL	64-17-5
ETHYL BENZENE	100-41-4
LIGHT PETROLEUM	8006-61-9
DISTILLATE	
N-HEXANE	110-54-3
NAPHTHALENE	91-20-3
TERT-BUTYL ALCOHOL	75-65-0
TOLUENE	108-88-3
BENZENE	71-43-2
BENZENE	71-43-2
CUMENE	98-82-8
CUMENE	98-82-8
CYCLOHEXANE	110-82-7
CYCLOHEXANE	110-82-7
ETHYL BENZENE	100-41-4
ETHYL BENZENE	100-41-4
	110-54-3
N-HEXANE NAPHTHALENE	110-54-3 91-20-3
	6

CERCLA/SARA - Haz Substances and their RQs CERCLA/SARA - Section 313 - Emission Reporting CWA (Clean Water Act) - Hazardous Substances CWA (Clean Water Act) - Priority Pollutants CWA (Clean Water Act) - Toxic Pollutants IARC - Group 1 (carcinogenic to humans) IARC - Group 2B (Possibly carcinogenic to humans) IARC - Group 2B (Possibly carcinogenic to humans) IARC - Group 2B (Possibly carcinogenic to humans) IARC - Group 3 (not classifiable) IARC - Group 3 (not classifiable) Inventory - Australia (AICS) Inventory - Canada - Domestic Substances List Inventory - Canada - Domestic Substances List

NAPHTHALENE	
	91-20-3
TOLUENE	
	108-88-3
TOLUENE	108-88-3
XYLENE	1330-20-7
XYLENE	1330-20-7
1,2,4-TRIMETHYLBENZENE	95-63-6
BENZENE	71-43-2
CUMENE	98-82-8
CYCLOHEXANE	110-82-7
ETHYL BENZENE	100-41-4
N-HEXANE	110-54-3
NAPHTHALENE	91-20-3
TERT-BUTYL ALCOHOL	75-65-0
TOLUENE	108-88-3
XYLENE	1330-20-7
BENZENE	71-43-2
	-
CYCLOHEXANE	110-82-7
ETHYL BENZENE	100-41-4
NAPHTHALENE	91-20-3
TOLUENE	108-88-3
XYLENE	1330-20-7
BENZENE	71-43-2
ETHYL BENZENE	100-41-4
NAPHTHALENE	91-20-3
TOLUENE	108-88-3
BENZENE	71-43-2
ETHYL BENZENE	100-41-4
NAPHTHALENE	91-20-3
TOLUENE	108-88-3
BENZENE	71-43-2
	-
ETHYL BENZENE	100-41-4
LIGHT PETROLEUM	8006-61-9
DISTILLATE	
NAPHTHALENE	91-20-3
TOLUENE	108-88-3
XYLENE	1330-20-7
1,2,4-TRIMETHYLBENZENE	
	95-63-6
2,6-DI-TERT-	95-63-6 128-39-2
2,6-DI-TERT-	
2,6-DI-TERT- BUTYLPHENOL	128-39-2
2,6-DI-TERT- BUTYLPHENOL BENZENE	128-39-2 71-43-2
2,6-DI-TERT- BUTYLPHENOL BENZENE CUMENE	128-39-2 71-43-2 98-82-8
2,6-DI-TERT- BUTYLPHENOL BENZENE CUMENE CYCLOHEXANE	128-39-2 71-43-2 98-82-8 110-82-7
2,6-DI-TERT- BUTYLPHENOL BENZENE CUMENE	128-39-2 71-43-2 98-82-8
2,6-DI-TERT- BUTYLPHENOL BENZENE CUMENE CYCLOHEXANE	128-39-2 71-43-2 98-82-8 110-82-7
2,6-DI-TERT- BUTYLPHENOL BENZENE CUMENE CYCLOHEXANE ETHYL ALCOHOL ETHYL BENZENE	128-39-2 71-43-2 98-82-8 110-82-7 64-17-5 100-41-4
2,6-DI-TERT- BUTYLPHENOL BENZENE CUMENE CYCLOHEXANE ETHYL ALCOHOL ETHYL BENZENE LIGHT PETROLEUM	128-39-2 71-43-2 98-82-8 110-82-7 64-17-5
2,6-DI-TERT- BUTYLPHENOL BENZENE CUMENE CYCLOHEXANE ETHYL ALCOHOL ETHYL BENZENE LIGHT PETROLEUM DISTILLATE	128-39-2 71-43-2 98-82-8 110-82-7 64-17-5 100-41-4 8006-61-9
2,6-DI-TERT- BUTYLPHENOL BENZENE CUMENE CYCLOHEXANE ETHYL ALCOHOL ETHYL BENZENE LIGHT PETROLEUM DISTILLATE N-HEXANE	128-39-2 71-43-2 98-82-8 110-82-7 64-17-5 100-41-4 8006-61-9 110-54-3
2,6-DI-TERT- BUTYLPHENOL BENZENE CUMENE CYCLOHEXANE ETHYL ALCOHOL ETHYL BENZENE LIGHT PETROLEUM DISTILLATE N-HEXANE NAPHTHALENE	128-39-2 71-43-2 98-82-8 110-82-7 64-17-5 100-41-4 8006-61-9 110-54-3 91-20-3
2,6-DI-TERT- BUTYLPHENOL BENZENE CUMENE CYCLOHEXANE ETHYL ALCOHOL ETHYL BENZENE LIGHT PETROLEUM DISTILLATE N-HEXANE	128-39-2 71-43-2 98-82-8 110-82-7 64-17-5 100-41-4 8006-61-9 110-54-3
2,6-DI-TERT- BUTYLPHENOL BENZENE CUMENE CYCLOHEXANE ETHYL ALCOHOL ETHYL BENZENE LIGHT PETROLEUM DISTILLATE N-HEXANE NAPHTHALENE TERT-BUTYL ALCOHOL	128-39-2 71-43-2 98-82-8 110-82-7 64-17-5 100-41-4 8006-61-9 110-54-3 91-20-3 75-65-0
2,6-DI-TERT- BUTYLPHENOL BENZENE CUMENE CYCLOHEXANE ETHYL ALCOHOL ETHYL BENZENE LIGHT PETROLEUM DISTILLATE N-HEXANE NAPHTHALENE TERT-BUTYL ALCOHOL TOLUENE	128-39-2 71-43-2 98-82-8 110-82-7 64-17-5 100-41-4 8006-61-9 110-54-3 91-20-3 75-65-0 108-88-3
2,6-DI-TERT- BUTYLPHENOL BENZENE CUMENE CYCLOHEXANE ETHYL ALCOHOL ETHYL BENZENE LIGHT PETROLEUM DISTILLATE N-HEXANE NAPHTHALENE TERT-BUTYL ALCOHOL TOLUENE XYLENE	128-39-2 71-43-2 98-82-8 110-82-7 64-17-5 100-41-4 8006-61-9 110-54-3 91-20-3 75-65-0 108-88-3 1330-20-7
2,6-DI-TERT- BUTYLPHENOL BENZENE CUMENE CYCLOHEXANE ETHYL ALCOHOL ETHYL BENZENE LIGHT PETROLEUM DISTILLATE N-HEXANE NAPHTHALENE TERT-BUTYL ALCOHOL TOLUENE XYLENE 1,2,4-TRIMETHYLBENZENE	128-39-2 71-43-2 98-82-8 110-82-7 64-17-5 100-41-4 8006-61-9 110-54-3 91-20-3 75-65-0 108-88-3 1330-20-7 95-63-6
2,6-DI-TERT- BUTYLPHENOL BENZENE CUMENE CYCLOHEXANE ETHYL ALCOHOL ETHYL BENZENE LIGHT PETROLEUM DISTILLATE N-HEXANE NAPHTHALENE TERT-BUTYL ALCOHOL TOLUENE XYLENE 1,2,4-TRIMETHYLBENZENE 2,6-DI-TERT-	128-39-2 71-43-2 98-82-8 110-82-7 64-17-5 100-41-4 8006-61-9 110-54-3 91-20-3 75-65-0 108-88-3 1330-20-7
2,6-DI-TERT- BUTYLPHENOL BENZENE CUMENE CYCLOHEXANE ETHYL ALCOHOL ETHYL BENZENE LIGHT PETROLEUM DISTILLATE N-HEXANE NAPHTHALENE TERT-BUTYL ALCOHOL TOLUENE XYLENE 1,2,4-TRIMETHYLBENZENE	128-39-2 71-43-2 98-82-8 110-82-7 64-17-5 100-41-4 8006-61-9 110-54-3 91-20-3 75-65-0 108-88-3 1330-20-7 95-63-6
2,6-DI-TERT- BUTYLPHENOL BENZENE CUMENE CYCLOHEXANE ETHYL ALCOHOL ETHYL BENZENE LIGHT PETROLEUM DISTILLATE N-HEXANE NAPHTHALENE TERT-BUTYL ALCOHOL TOLUENE XYLENE 1,2,4-TRIMETHYLBENZENE 2,6-DI-TERT-	128-39-2 71-43-2 98-82-8 110-82-7 64-17-5 100-41-4 8006-61-9 110-54-3 91-20-3 75-65-0 108-88-3 1330-20-7 95-63-6
2,6-DI-TERT- BUTYLPHENOL BENZENE CUMENE CYCLOHEXANE ETHYL ALCOHOL ETHYL BENZENE LIGHT PETROLEUM DISTILLATE N-HEXANE NAPHTHALENE TERT-BUTYL ALCOHOL TOLUENE XYLENE 1,2,4-TRIMETHYLBENZENE 2,6-DI-TERT- BUTYLPHENOL BENZENE	128-39-2 71-43-2 98-82-8 110-82-7 64-17-5 100-41-4 8006-61-9 110-54-3 91-20-3 75-65-0 108-88-3 1330-20-7 95-63-6 128-39-2 71-43-2
2,6-DI-TERT- BUTYLPHENOL BENZENE CUMENE CYCLOHEXANE ETHYL ALCOHOL ETHYL BENZENE LIGHT PETROLEUM DISTILLATE N-HEXANE NAPHTHALENE TERT-BUTYL ALCOHOL TOLUENE XYLENE 1,2,4-TRIMETHYLBENZENE 2,6-DI-TERT- BUTYLPHENOL BENZENE CUMENE	128-39-2 71-43-2 98-82-8 110-82-7 64-17-5 100-41-4 8006-61-9 110-54-3 91-20-3 75-65-0 108-88-3 1330-20-7 95-63-6 128-39-2 71-43-2 98-82-8
2,6-DI-TERT- BUTYLPHENOL BENZENE CUMENE CYCLOHEXANE ETHYL ALCOHOL ETHYL BENZENE LIGHT PETROLEUM DISTILLATE N-HEXANE NAPHTHALENE TERT-BUTYL ALCOHOL TOLUENE XYLENE 1,2,4-TRIMETHYLBENZENE 2,6-DI-TERT- BUTYLPHENOL BENZENE CUMENE CYCLOHEXANE	128-39-2 71-43-2 98-82-8 110-82-7 64-17-5 100-41-4 8006-61-9 110-54-3 91-20-3 75-65-0 108-88-3 1330-20-7 95-63-6 128-39-2 71-43-2 98-82-8 110-82-7
2,6-DI-TERT- BUTYLPHENOL BENZENE CUMENE CYCLOHEXANE ETHYL ALCOHOL ETHYL BENZENE LIGHT PETROLEUM DISTILLATE N-HEXANE NAPHTHALENE TERT-BUTYL ALCOHOL TOLUENE XYLENE 1,2,4-TRIMETHYLBENZENE 2,6-DI-TERT- BUTYLPHENOL BENZENE CUMENE CYCLOHEXANE ETHYL ALCOHOL	128-39-2 71-43-2 98-82-8 110-82-7 64-17-5 100-41-4 8006-61-9 110-54-3 91-20-3 75-65-0 108-88-3 1330-20-7 95-63-6 128-39-2 71-43-2 98-82-8 110-82-7 64-17-5
2,6-DI-TERT- BUTYLPHENOL BENZENE CUMENE CYCLOHEXANE ETHYL ALCOHOL ETHYL BENZENE LIGHT PETROLEUM DISTILLATE N-HEXANE NAPHTHALENE TERT-BUTYL ALCOHOL TOLUENE XYLENE 1,2,4-TRIMETHYLBENZENE 2,6-DI-TERT- BUTYLPHENOL BENZENE CUMENE CYCLOHEXANE ETHYL ALCOHOL ETHYL BENZENE	128-39-2 71-43-2 98-82-8 110-82-7 64-17-5 100-41-4 8006-61-9 110-54-3 91-20-3 75-65-0 108-88-3 1330-20-7 95-63-6 128-39-2 71-43-2 98-82-8 110-82-7 64-17-5 100-41-4
2,6-DI-TERT- BUTYLPHENOL BENZENE CUMENE CYCLOHEXANE ETHYL ALCOHOL ETHYL BENZENE LIGHT PETROLEUM DISTILLATE N-HEXANE NAPHTHALENE TERT-BUTYL ALCOHOL TOLUENE XYLENE 1,2,4-TRIMETHYLBENZENE 2,6-DI-TERT- BUTYLPHENOL BENZENE CUMENE CYCLOHEXANE ETHYL ALCOHOL	128-39-2 71-43-2 98-82-8 110-82-7 64-17-5 100-41-4 8006-61-9 110-54-3 91-20-3 75-65-0 108-88-3 1330-20-7 95-63-6 128-39-2 71-43-2 98-82-8 110-82-7 64-17-5
2,6-DI-TERT- BUTYLPHENOL BENZENE CUMENE CYCLOHEXANE ETHYL ALCOHOL ETHYL BENZENE LIGHT PETROLEUM DISTILLATE N-HEXANE NAPHTHALENE TERT-BUTYL ALCOHOL TOLUENE XYLENE 1,2,4-TRIMETHYLBENZENE 2,6-DI-TERT- BUTYLPHENOL BENZENE CUMENE CYCLOHEXANE ETHYL ALCOHOL ETHYL BENZENE	128-39-2 71-43-2 98-82-8 110-82-7 64-17-5 100-41-4 8006-61-9 110-54-3 91-20-3 75-65-0 108-88-3 1330-20-7 95-63-6 128-39-2 71-43-2 98-82-8 110-82-7 64-17-5 100-41-4

Inventory - Canada - Domestic Substances List Inventory - China Inventory - European EINECS Inventory Inventory - Japan - (ENCS) Inventory - Korea - Existing and Evaluated Inventory - Korea - Existing and Evaluated

N-HEXANE 110-54-3 NAPHTHALENE 91-20-3 **TERT-BUTYL ALCOHOL** 75-65-0 108-88-3 TOLUENE XYLENE 1330-20-7 1,2,4-TRIMETHYLBENZENE 95-63-6 128-39-2 2,6-DI-TERT-BUTYLPHENOL 71-43-2 BENZENE CUMENE 98-82-8 **CYCLOHEXANE** 110-82-7 ETHYL ALCOHOL 64-17-5 ETHYL BENZENE 100-41-4 LIGHT PETROLEUM 8006-61-9 DISTILLATE 110-54-3 N-HEXANE 91-20-3 NAPHTHALENE **TERT-BUTYL ALCOHOL** 75-65-0 TOLUENE 108-88-3 1330-20-7 XYLENE 1,2,4-TRIMETHYLBENZENE 95-63-6 2.6-DI-TERT-128-39-2 BUTYLPHENOL BENZENE 71-43-2 CUMENE 98-82-8 **CYCLOHEXANE** 110-82-7 ETHYL ALCOHOL 64-17-5 ETHYL BENZENE 100-41-4 8006-61-9 LIGHT PETROLEUM DISTILLATE 110-54-3 N-HEXANE NAPHTHALENE 91-20-3 **TERT-BUTYL ALCOHOL** 75-65-0 TOLUENE 108-88-3 **XYLENE** 1330-20-7 1,2,4-TRIMETHYLBENZENE 95-63-6 128-39-2 2,6-DI-TERT-BUTYLPHENOL 71-43-2 BENZENE CUMENE 98-82-8 **CYCLOHEXANE** 110-82-7 64-17-5 ETHYL ALCOHOL ETHYL BENZENE 100-41-4 N-HEXANE 110-54-3 91-20-3 NAPHTHALENE **TERT-BUTYL ALCOHOL** 75-65-0 108-88-3 TOLUENE **XYLENE** 1330-20-7 1,2,4-TRIMETHYLBENZENE 95-63-6 128-39-2 2,6-DI-TERT-BUTYLPHENOL BENZENE 71-43-2 CUMENE 98-82-8 CYCLOHEXANE 110-82-7 ETHYL ALCOHOL 64-17-5 ETHYL BENZENE 100-41-4 LIGHT PETROLEUM 8006-61-9 DISTILLATE 110-54-3 N-HEXANE 91-20-3 NAPHTHALENE **TERT-BUTYL ALCOHOL** 75-65-0 Inventory - Korea - Existing and Evaluated Inventory - Korea - Existing and Evaluated Inventory - Philippines Inventory (PICCS) Inventory - TSCA - Sect. 8(b) Inventory Massachusetts - Right To Know List New Jersey - Department of Health RTK List New Jersey - Env Hazardous Substances List New Jersey - Env Hazardous Substances List New Jersey - Env Hazardous Substances List

TOLUENE	100 00 2
	108-88-3
XYLENE	1330-20-7
1,2,4-TRIMETHYLBENZENE	95-63-6
2,6-DI-TERT-	128-39-2
BUTYLPHENOL	
BENZENE	71-43-2
CUMENE	98-82-8
CYCLOHEXANE	110-82-7
ETHYL ALCOHOL	64-17-5
ETHYL BENZENE	100-41-4
LIGHT PETROLEUM	8006-61-9
DISTILLATE	
N-HEXANE	110-54-3
NAPHTHALENE	91-20-3
TERT-BUTYL ALCOHOL	75-65-0
TOLUENE	108-88-3
XYLENE	1330-20-7
1,2,4-TRIMETHYLBENZENE	95-63-6
2,6-DI-TERT-	128-39-2
BUTYLPHENOL	
BENZENE	71-43-2
CUMENE	98-82-8
CYCLOHEXANE	110-82-7
ETHYL ALCOHOL	64-17-5
ETHYL BENZENE	100-41-4
	8006-61-9
DISTILLATE	
N-HEXANE	110-54-3
NAPHTHALENE	91-20-3
TERT-BUTYL ALCOHOL	75-65-0
TOLUENE	108-88-3
XYLENE	1330-20-7
1,2,4-TRIMETHYLBENZENE	95-63-6
BENZENE	71-43-2
	-
CUMENE	98-82-8
CYCLOHEXANE	110-82-7
ETHYL ALCOHOL	64-17-5
ETHYL BENZENE	100-41-4
LIGHT PETROLEUM	8006-61-9
DISTILLATE	
N-HEXANE	110-54-3
NAPHTHALENE	91-20-3
TERT-BUTYL ALCOHOL	75-65-0
TOLUENE	
	108-88-3
XYLENE	1330-20-7
1,2,4-TRIMETHYLBENZENE	95-63-6
BENZENE	71-43-2
CUMENE	98-82-8
CYCLOHEXANE	110-82-7
ETHYL ALCOHOL	64-17-5
ETHYL BENZENE	100-41-4
LIGHT PETROLEUM	8006-61-9
	0000-01-9
DISTILLATE	
N-HEXANE	110-54-3
NAPHTHALENE	91-20-3
TERT-BUTYL ALCOHOL	75-65-0
TOLUENE	108-88-3
XYLENE	
	1330-20-7
CYCLOHEXANE	
CYCLOHEXANE ETHYL BENZENE	110-82-7
CYCLOHEXANE ETHYL BENZENE N-HEXANE	

New Jersey - Env Hazardous Substances List TOLUENE 108	8-88-3
	0-00-0
New Jersey - Env Hazardous Substances List XYLENE 1330)-20-7
New Jersey - Special Hazardous Substances BENZENE 7'	-43-2
	8-82-8
)-82-7
	-17-5
)-41-4
	61-9
DISTILLATE	
)-54-3
	5-65-0
	8-88-3
)-20-7
	-43-2
	-43-2
	-43-2 8-88-3
	-00-3 3-82-8
	-43-2
0 0	8-82-8
8 8)-82-7
8 8	-17-5
8 8)-41-4
)-54-3
	-20-3
	5-65-0
8 8	8-88-3
8 8)-20-7
0 0	-43-2
•	-43-2
	5-63-6
	-43-2
Pennsylvania - RTK (Right to Know) List CUMENE 98	8-82-8
Pennsylvania - RTK (Right to Know) List CYCLOHEXANE 110)-82-7
	-17-5
Pennsylvania - RTK (Right to Know) List ETHYL BENZENE 100)-41-4
Pennsylvania - RTK (Right to Know) List N-HEXANE 110)-54-3
Pennsylvania - RTK (Right to Know) List NAPHTHALENE 9'	-20-3
Pennsylvania - RTK (Right to Know) List TERT-BUTYL ALCOHOL 75	5-65-0
Pennsylvania - RTK (Right to Know) List TOLUENE 108	8-88-3
)-20-7
	-43-2
)-82-7
)-54-3
	-20-3
	5-65-0

Title III Classifications Sections 311,312:

- Acute: YES
- Chronic: YES
- Fire: YES
- Reactivity: NO
- Sudden Release of Pressure: NO

15. OTHER INFORMATION

Precautionary labeling for pumps, portable containers, and drums is required. A "hazardous when empty" pictogram and D.O.T. flammable liquid label are also required for drums. Details available upon request. Because benzene is present in this product above 0.1%, the Osha Standard for benzene is applicable to work locations upstream of final

discharge from terminals. Consult 29CFR1910.1028 for details. Prolonged and repeated excessive exposures to benzene can result in blood disorders ranging from anemia to leukemia. Sun recommends that exposures to benzene be kept below 1.0 ppm for 8-hours; 5.0 ppm for 15-min. Normal service station operations are below these values. For use as motor fuel only. Do not use for any other purpose. Catecholamines and similar adrenergic drugs are generally contraindicated because of potential for increased sensitivity of the heart from hydrocarbon overexposure and subsequent ventricular fibrillation. EKG monitoring may be indicated and bronchodilators should be selected with care. Following injection, prompt debridement of the wound is necessary to minimize necrosis and tissue loss. COMPONENT TOXICITY: Overexposure to naphthalene, a minor component of this product, may cause skin, eye and respiratory tract irritation, anemia, loss of vision, nervous system effects and kidney and thymus damage. Also, exposure to naphthalene has produced "respiratory tract" tumors in laboratory animals.. Cumene may be harmful or fatal if swallowed. Pulmonary aspiration hazard. After ingestion, may enter lungs and cause damage. May cause respiratory irritation, fluid in the lungs and lung damage. May be irritating to the skin and eyes. May be harmful if absorbed through the skin. May cause nervous system effects, including drowsiness, dizziness, coma and even death. Overexposure has caused blood changes and kidney, spleen and liver damage in laboratory animals. Hours of exposure to high airborne concentrations of xylene, a minor component of this product, has caused a hearing loss in laboratory animals.